

Model: SAVAGE DARK POLISHED 120X120 (6)(A)

Codes: 100181604

Absorption: Bla - Porcelánico (E<=0.1%)



## DIMENSIONAL FEATURES

Length	47 1/4" approx	
Thickness	1/4" approx	
Width	47 1/4" approx	
Length and width deviation	Below 0.15%	+/-0.3%*
Side straightness deviation	Below 0.15%	+/-0.3%*
Squareness deviation	Below 0.15%	+/-0.3%*
Surface flatness deviation	Below 0.15%	+/-0.4%*

## MECHANICAL FEATURES

Breaking strenght	>1100 N	
Modulus of rupture	>45 N/MM2	
Abrasion resistance	<140	

## HYGIENIC FEATURES

Chemical resistance	MIN B	
Stain resistance	5	

## ANTI-SLIP VALUE

Slip resistance (pendulum-wet)	CL0	
Stain resistance	5	
4s	DRY>36-LOW_WET<25-HIGH	

## SCOPE OF USE

Technical code-1	Use on light traffic floors	
Technical code-2	Dry interior floors	

## PACKING

Sales units per box	31 SQF/CS	
Sales units per pallet	806 SQF/PAL	
Sales units per unit	15.5 SQF/ST	

## ADDITIONAL NOTES

COMPOSITION CONTINUITY, MAXIMUM DEVIATION OF IMAGE 3CM

### System Certification



Do not use cleaning agents containing hydrofluoric acid.

It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint.

For big sizes, it is recommended to fix with mortars containing polymeric additives and to use the double gluing technique.

Mosaic tiles must be grouted.

This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.